

Powered by
Kawasaki

 **MODENAS**



Ninja **250**
ABS

EMOS

MODEL SPECIFICATIONS

ENGINE

Type	4-Stroke, 2-Cylinder, DOHC, 4-Valve, Liquid Cooled
Displacement	249 cc
Bore x Stroke	62.0mm x 41.2mm
Compression Ratio	11.6:1
Fuel Supply	Fuel Injection
Lubrication System	Forced Wet Sump
Starting System	Electric Starter
Ignition System	B&C (TCBI, B, P&EL, ADV.D.)

FRAME

Type	Trellis, High-Tensile Steel	
Suspension:	Front	Telescopic Fork
	Rear	Mono Shock
Wheel Travel:	Front	120mm
	Rear	130mm
Caster (Rake Angle)	24.3	
Trail	90mm	
Steering Angle (left/right)	35/35	
Tyre:	Front	110/70-17M/C 54H
	Rear	140/70-17M/C 66H
Brake:	Front	Single Disc (310mm)
	Rear	Single Disc (220mm)

DIMENSIONS

Overall Length	1990mm
Overall Width	710mm
Overall Height	1125mm
Wheelbase	1370mm
Road Clearance	145mm
Seat Height	795mm
Curb Mass	167kg
Fuel Capacity	14 liters

DRIVETRAIN

Driving System	Chain
Transmission	6-speed, Constant Mesh, Return Shift
Primary Reduction ratio	3.069(89/29)
Final Reduction ratio	2.857(40/14)
Clutch Type (Primary)	Wet, Multi-disc

PERFORMANCE

Max. Power	27.5kW@12,500 rpm
Max. Torque	23.0Nm@10,000 rpm

LIGHT

Headlight (High/Low)	LED/LED
Brake/Tail Light	LED

Ninja 250

ABS



Lime Green / Ebony



* Specifications are subject to change without prior notice

** Pictures displayed are for illustration purposes only. Actual product may vary.

Kawasaki Technology



EMOS

A Wholly Owned Subsidiary of MODENAS

EON Head Office Complex, Level 2, No. 2, Parsiaran Kerjaya, Taman Perindustrian Glenmarie, Seksyen U1, 40150 Shah Alam, Selangor Darul Ehsan, Malaysia.

Kawasaki WhatsApp Care Line :
+6019 570 8135

Kawasaki Toll Free Line :
+1800 880 008

www.kawasaki.com.my

[kawasakimotors.my](https://www.facebook.com/kawasakimotors.my)

[kawasakimotors.my](https://www.instagram.com/kawasakimotors.my)