



ENGINEERED TO BE FREE



MODEL SPECIFICATIONS



			DIMENSIONS		
уре		4-stroke, In-line 4-cylinder, DOHC,	Overall Length	2,175 mm	
, po		16-valve, liquid-cooled	Overall Width	790 mm	
isplacement		998cc	Overall Height	1,260 mm	Kewnsaki
ore X Stroke		76.0 x 55.0mm	Wheelbase	1,480 mm	
ompression Ratio		11.2:1	Road Clearance	130 mm	
uel Supply		DFI® with 40mm throttle bodies (4);	Seat Height	835 mm	
		Kawasaki Supercharger	Curb Mass	267 kg	
ubrication System		Forced Lub. Wet	Fuel Capacity	19 litres	
tarting System		EL. Starter			
nition System		TCBI with Digital Advance	DRIVETRAIN		
RAME			Driving System	Chain	
		Trallia kink toraile steal with anti-	Transmission	6-speed, Return Shift	
уре		Trellis, high-tensile steel, with swingarm mounting plate	Primary Reduction ratio	1.480 (74/50)	
uspension: Fr	ront	43mm inverted Showa fork with KECS-	Final Reduction ratio	2.444 (44/18)	Emerald Blazed Green/Metallic Diablo Black
		controlled rebound and compression	Clutch Type (Primary)	Wet Multi-Disc, Manual	Metallic Matte Graphenesteel Gray
		damping, manual spring preload			
		adjustability and top-out springs.	PERFORMANCE		
Re	ear	Uni-Trak®, Showa BFRC lite gas-charged	Max. Power	147 kW / 11,000 rpm	
		shock with piggyback reservoir, KECS-	(with Ram Air)	(154 kW / 11,000 rpm)	Kawasal
		controlled compression and rebound	Max. Torque	137 N∙m / 8,500 rpm	
		damping electronically-adjustable	SPECIAL FEATURES	i i shuki na shiki a la sa ka	
/heel Travel: Fr	ront	spring preload/5.5 inspring. 120 mm			
	ear	139 mm		Full-color TFT Instrumentation,	
aster (Rake Angle)	cui	24.7°		Cornering Lights, Kawasaki's	
teering Angle (left/right)		30° / 30°	Intelligent Proximity Activation Start System (KIPASS), Highly Durable Paint, Grip heaters, Tire Pressure Monitoring		
0 0 1	ront	120/70-17		ne Connectivity via Kawasaki	
	ear	190/55-17	SPIN infotainment app		
Brakes: Fr	ront	Dual 320mm semi-floating discs with dual radial-mount, opposed 4-piston Brembo Stylema® calipers,			
		Kawasaki Intelligent anti-lock Brake System (KIBS)			
Re	ear	Single 250mm disc with opposed 2-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)		anti-lock Brake System (KIBS)	

* Specifications are subject to change without prior notice

** Pictures displayed are for illustration purposes only. Actual product may vary.

Kawasaki Technology







5



EMOS Edaran Modenas Sdn. Bhd. The Distribution Arm of MODENAS

EON Head Office Complex, Level 2, No. 2, Persiaran Kerjaya, Taman Perindustrian Glenmarie, Seksyen UI, 40150 Shah Alam, Selangor Darul Ehsan, Malaysia.

Kawasaki WhatsApp Care Line : +6019 570 8135





